


Tiger DR-Wired & Wireless Options for Chiropractics

(Sizes 17"x17", 14"x17" & 10"x12")

Acquire | Store | View | Share

Cassette Size Flat Panel Detector



Simple, easy, and cost-effective CSI DR Solutions

Three size options in both wired and wireless



8 lbs, with easy access handle



3 sizes both wired and wireless (17"x17", 14"x17" and 10"x12")



8 second image acquisition time



Directly integrates with TigerView



No cassettes necessary



3 year warranty

Tiger DR Cesium benefits include:

- Highest DQE and the best MTF among CsI detectors
- Superior Cesium Iodide (CsI) construction
- Rapid image acquisition in 8 seconds
- Up to 7 hours battery life with the Wireless Option
- Simple magnetic cable connection for easy charging



Tiger DR-Wired & Wireless Options for Orthopedics

(Sizes 17"x17", 14"x17" & 10"x12")

Cassette Size Flat Panel Detector

SPECIFICATIONS

Sensor		Environmental	
Sensor	a-Si TFT Array	Operating	
Conversion Screen	CsI: Ti / Premium Gadox	Temperature Range	10 - 35°C
Image Data	16bits	Humidity Range (non-condensing)	20% - 75% RH
Limiting Resolution	3.5 lp/mm	Storage	
14x17 Active Area	14 x 17 in (350x430 mm)	Temperature Range	-10°C - 60°C
14x17 Sensor Pixel	2560 x 3072	Humidity Range	10% - 90% RH
Image Quality		Mechanical	
Data Transfer Time	Less than 1 second	14x17 Dimensions	385 x 460 x 15mm
Internal Storage	Up to 200	14x17 Weight	6 lbs w/battery
Communication Interface		Power	
Image Acquisition Time	3-5 sec. (approx)	Battery Performance	10 hours
Data Transfer Time	Less than 1 second	AC Power	
Trigger Mode	AED (Auto Exposure Detection), Manual Trigger	Power Supply	100 - 240V AC
Calibration Mode	ACC (Auto Calibration Control), Manual Calibration	Frequency	50/60 Hz
Image Transmission	Gigabit Wi-Fi IEEE 802.11		

