

Tiger DRX-C Podiatry



Most Advanced Cesium Flat Panel DR & X-Cel X-Ray Solution



The Industry Leading DR and Podiatry PACS Solution

Tiger DRX-C is the only true DR Panel X-Ray detector solution for the podiatry market. Using modern CESIUM technology provides superior image quality. Tiger DRX-C allows podiatrists the logical and modern solution when converting to Digital X-Ray or upgrading from older technology.

Tiger DRX-C comes with a handled detector encasement that is designed for increased maneuverability and durability. Our specialized encasement has been designed to fit exclusively into our ADA conformant orthoposer. At 3.5" tall, it's simple to position patients using X-Cel's exclusive tilt-head, bi-directional functionality.

TigerView is a Podiatry Specific PACS software that understands the needs of the practitioner and has been developed with 30+ different podiatry measurements. Comprehensive AP and Lateral tool sets provide for quick and efficient patient diagnosis. Reward yourself with the newest and most logical workflow designed to simplify the experience and enhance the interaction as you look at superior image quality.

Tigerview offers complete turn-key solutions. Available upgrades to the DRX-C solution: Wireless panel, TigerView CLOUD, TigerView Mobile, TigerView Portal and TigerView back-up.

Standard Tigerview X-Cel packages include:

- X-Cel bi-directional x-ray generator
- X-Cel ADA compliant ortho-base
- X-Cel ergonomic panel encasement
- 23" computer
- TigerView Podiatry PACS software
- Five viewing software licenses
- Bridges to EMR, EHS & PMS
- On-site install and training

5 lbs

Panel available tethered or wireless

6 second image acquisition time

Directly integrates with TigerView software

No cassettes necessary

2 year x-ray Electrical
5 year x-ray Mechanical
5 year panel warranty

X-Cel bi-directional tilt-head x-ray included

Call us for an in-office demo today

1-800-385-9593



RAYTECH-DIAGNOSTICS

613-799-4171

sales@raytechdiagnostics.com

[https://raytechdiagnostics.com](http://raytechdiagnostics.com)

Tiger DRX-C Podiatry

Most Advanced Cesium Flat Panel DR & X-Cel X-Ray Solution

SPECIFICATIONS

Sensor		Environmental	
Scintillator	CsI	Operating	
Active Area	307 x 246 mm ²	Temperature Range	0 - 40°C
Pixel Array	2560 x 2048	Humidity Range (non-condensing)	30% - 75% RH
Pixel Pitch	120 µm	Storage	
Image Quality		Temperature Range	-20°C - 55°C
Limiting Resolution	>4.2 lp	Humidity Range	10% - 90% RH
MTF	70% (@1 lp/mm)	Water / Dust Proof	IP64
	40% (@2 lp/mm)		
	25% (@3 lp/mm)		
	15% (@4 lp/mm)		
DQE (RQA5, 14µGy)	~70% (@0 lp/mm) ~33% (@3 lp/mm)	Mechanical	
Sensitivity	~0.62ct/nGy	Dimensions	33.3 x 28.2 x 1.5 cm ²
Response Non-linearity	< ±0.5%	Weight	~2.3 kg
Maximum Linear Dose	> 95µGy	Housing Material	Front: Carbon Fiber Back: Aluminum Alloy
Dark Noise	~ 10nGy	Power	
Dynamic Range	~ 82 dB	Maximum Power	Standby: 8W Operating: 17W
Communication Interface		AC Power	
Image Acquisition Time	8 seconds	Power Supply	100 - 240V AC
Exposure Control	F ² AED External Sync/Manual	Frequency	50/50 Hz
Communication Interface	WiFi/Gigabit Ethernet	Battery	3200 mAH, 14.7V



Call us for an in-office demo today
1-800-385-9593

RAYTECH-DIAGNOSTICS
613-799-4171
sales@raytechdiagnostics.com
<https://raytechdiagnostics.com>